

SPRAY LUBE

SOLUTIONS




ALU-TECH > Specially formulated high temperature **anti-weld thread lubricant**, which will prevent seizure and damage on all threaded connections at temperatures up to 1200°C without

melting, and in corrosive conditions. This product is completely lead free, safe to use and offers visual clarity on surfaces to which it is applied.



COPPER-TECH > **Anti-seize paste** containing particles of pure copper combined with high quality micron sized synthetic graphite, blended into a non-melting base.

This special blend aids assembly and provides long lasting protection against seizure in corrosive environments, even up to 1100°C. Ideal on threaded fasteners and close mating surfaces.



MOLY-TECH AP > Extreme load low friction **assembly and running in paste** for use under the most severe conditions. Manufactured using a non-melting base with a high concentration of

MoS₂, it will operate at temperatures up to 550°C. It prevents scuffing and fretting corrosion caused by metal to metal contact and its long life lubricating film gives trouble free assembly and dismantling.



BELT-TECH > Specially designed **anti-slip belt coating** producing more effective life from leather, rubber and synthetic belts, whether round or flat. An application of Belt-Tech will give improved

grip which will allow the belt to transmit full power without slipping. The spray pattern of this aerosol allows easy application through guards.



DRY-GRAF > Bonded **dry graphite lubricant coating** which gives a dry film without baking. The low friction coating eliminates problems associated with oil and grease lubrication where dirt and debris

sticks to surfaces. When dry, the coating will withstand temperatures up to 650°C. Also available in bulk.



CITRO-TECH > Specially formulated water based **hard surface cleaner**, perfect for the removal of heavy grease deposits from floors and other working areas.

Containing natural citric extracts, it has a pleasant odour and is very safe to use. Can be diluted with up to 40 parts water, depending on the severity of soiling.



ELEC-TECH > Highly refined **solvent cleaner** for use on electrical and electronic components. It can also be used for degreasing metal, plastic, painted and chlorinated rubber surfaces.

It contains no chlorinated solvents and evaporates quickly to leave a clean, dry surface. Not suitable for use on live electrics.



SURE-SLIDE > Bonded **dry PTFE coating** not requiring heat curing. It provides a smooth, long lasting, non-stick coating suitable for most surfaces.

The low coefficient of friction prevents adhesion of airborne debris and provides an easy sliding action, particularly on low loaded parts.



PEN-TECH > Technically advanced **penetrating fluid with PTFE** which gives fast results on even the most corroded components, reducing friction and displacing water. It is also an excellent

demoisturising spray ideal for use on electrical equipment, including automotive. Pen-Tech will clean and displace grease and abrasive particles from metal surfaces, leaving a protective shield of PTFE.

FS EASE > **Food safe dismantling fluid** formulated using clean, colourless semi-synthetic ingredients, designed to penetrate quickly and deeply. It is also used as a light lubricant for chains, pivot points

and delicate mechanisms. It is ideal for use in wet areas, dispersing water, lubricating and protecting surfaces from corrosion. FS-Ease is fully NSF H1 rated and Kosher approved.



FS EXTRA > Fully synthetic **food safe grease** using the latest technology of anti-oxidant, EP and PTFE blends. It is 100% resistant to both fresh and salt water and completely non-melting.

FS Extra is sprayed as a thin penetrating fluid which thickens inside bearings and chains reforming to a fully rated No 2 H1 grease, operating between -40°C and 280°C.




FS LUBE-FLOW > Clear, synthetic, odourless **food safe oil** used to lubricate chains, pivots and delicate mechanisms. Delivered by non-flammable aerosol, it is ideal for application to hot surfaces.

FS Lube-Flow is hydrophobic making it perfect for use in wet areas, lubricating and protecting metal surfaces from corrosion. FS Lube-Flow is NSF H1 rated and Kosher approved.



FS TROJAN > **New synthetic food grade grease** with extra high duty additives and the addition of PTFE to reduce friction. The latest Aluminium Complex Technology is used to provide a high

temperature lubricant, capable of meeting the most arduous and heavily loaded conditions found in all food factories, on both bearings and gears. FS Trojan is NSF H1 rated.



FS SILL-TECH > Food safe, multi-use, non-staining **silicone lubricant**. It is designed to impart non-stick properties and provide light lubrication to delicate mechanisms on all types of machinery.

FS Sill-Tech is ideal as a plastic mould release agent and as a lubricant on metal, plastic and rubber surfaces, particularly for food packaging. FS Sill-Tech is NSF H1 rated in spray and bulk.



FS CHAIN-TECH > Fully synthetic food safe **PTFE lubricating oil** suitable for food processing machinery. It allows penetration into chain links and intricate mechanisms leaving behind a clean, non-

toxic, anti-corrosive shield to give long term protection and lubrication of all sliding surfaces and rolling elements, which will not drip or fling off. NSF H1 and Kosher approved.




LINK-TECH > **Chain and rope spray** designed to lubricate chains and ropes operating in arduous conditions carrying excessive loads. Conventional oils and greases will not penetrate into links of

chains or strands of ropes but simply lie on the surface to attract dust or fling off. Link-Tech penetrates as a thin oil and then thickens to form a heavy duty lubricant where it is needed.



POWER-CUT > **Heavy duty cutting fluid** specially formulated to assist the machining of all types of metals, including stainless steel and aluminium. The extreme load carrying properties of

Power-Cut provide excellent adhesion to tool edges, which gives a superior finish to machine parts and extends tool life. Suitable for reaming, tapping, drilling and screw cutting.



SOLUTION 3 > **All weather gear and chain lubricant** fortified with graphite and MoS₂. It is delivered as a brown/black fluid to give even surface coating of gears and penetration into

chains. Solution 3 dries to form a tough, non-fling lubricating film which will not attract dust and dirt and will not be washed off even in the wettest conditions.

